

THERMO-TEC AUTOMOTIVE, INC.

WWW.THERMOTEC.COM

SAFETY DATA SHEET

SECTION I-Identification

Manufacturer: Address:

Thermo-Tec Automotive, INC. P. O. Box 96 Greenwich, OH 44837 800-274-8437 January I, 2022

Emergency/Health/Technical phone: Preparation/Revision Date: Product Identifier:

Recommended use:

Adhesive Backed Heat Barrier/ Thermo Shield

SDS

No use is specified

SECTION II-Hazardous Identification

Emergency Overview: Non-Hazardous Appearance and Odor: White in color in tape or fabric form; no odor. Primary Routes of Exposure: Skin, eyes and mouth Possible Health Effects: Inhalation: Mechanical irritation of the mouth, nose and throat. Mechanical irritation to the skin Skin contact: Eye contact: Mechanical irritation to the eyes Ingestion: Ingestion is not likely. Medical Conditions Aggravated by Exposure: Chronic respiratory and skin conditions may temporarily worsen from exposure IARC, ACHIH, NTP AND OSHA do not list fiberglass fabrics as a carci nogen Carcinogenicity: None known. See Section 11: Toxicological Information Chronic Conditions:

SECTION III - Composition and Ingredient Information

Name	OSHA P <u>EL</u>	ACGIH TLY	Other Limits Recommended	
Fibrous Glass	15 mg/M ³	10 mg/M^3	3 fibers/cc(NIOSH)	>95
(CAS #65997-17-3)	$(5 \text{ mg/M}^3 - \text{respirable dust})$			
Aluminum particles,				<10
sizings, binders				
(CAS not available)				
			-	

SECTION IV - First-Aid Measures

Inhalation:	Move person to fresh air, rinse mouth and blow nose to expel fibers.
Skin:	Wash with mild soap and running water. Do not rub or scratch affected area.
Eyes:	Flush with flowing water for at least 15 minutes and if symptoms persist, seek medical attention.
Ingestion:	If ingested and gastrointestinal irritation develops seek medical attention.

SECTION V-Fire-Fighting Measures

Flash Point:	N/A
Flammability classification:	Non-flammable
Unusual Fire and Explosion Hazards:	N/A
Extinguishing Techniques:	Use the appropriate technique for surrounding fire- Water, foam, C02 or dry
	chemical
Equipment:	Fire fighters should wear full protective gear including NIOSH approved sell
	contained breathing apparatus.
Chemical hazards from fire:	Fiberglass will not burn. However, thermal decomposition of fiber coatings may
	produce an irritating mixture of smoke and fumes. It may release carbon monoxide,
	carbon dioxide, and water.
	Page 1 o

Page 1 of 3

P.O. Box 96 Greenwich, OH 44837 T: 800-274-8437 F: 419-962-4013 www.thermotec.com



THERMO-TEC AUTOMOTIVE, INC.



SAFETY DATA SHEET

	SECTION VI - Accidental Release Measures		
Emergency procedures:	Fiberglass is considered an inert solid waste. Special procedures are not required.		
Protective equipment:	Wear appropriate personal protective equipment as stated in section VIII. Vacuum up dust. if sweeping is necessary, use a dust suppressant to avoid dust generation.		
Proper method of containment and cleanup:	Fiberglass is considered an inert solid non-hazardous waste. Dispose in accordance with federal state and local regulations.		
	SECTION VII - Handling and Storage		
-	prolonged contact with the skin to avoid irritation. Wear PPE as described in Section VIII when ary. Wash hands and face after handling product and before eating.		
Storing: Store away from direct sunlight in an area without excessive humidity to prevent damage to the product and packaging materials. To avoid damaging the material do not double stack.			
Incompatibili ties: N/A			
SECTION VIII-Exposure Controls and Personal Protection			
Name Fibrous Glass (CAS #65997-17-3) Sizings, Binders (CAS not available)	OSHA PEL ACG II-I TLV Other Limits Recommended 15 mg/M ³ 10 mg/M ³ 3 fibers/ cc(NIOSI-1) >95 (5 mg/M ³ - respirable dust) <5		
Engineering Controls:	N/A		
Respiratory Protection: Where dust levels exceed permissible exposure levels, use NIOSI-1 approved respiratory protection for nuisance dust			
Ventilation: Local	exhaust is recommended to control dust.		
Eye Protection: Not required unless fiber levels cause mechanical irritation. Wear safety glasses with side shields/goggles.			
Protective Gloves:	Wear gloves and use barrier creams, if necessary.		
Other Protective Clothing or equipment: Use of long sleeved shirts, buttoned to fit loosely at the neck and wrists. long pants, and good personal hygiene will maximize comfort. Separate contaminated work clothes from street clothes and launder separately.			

SECTION IX- Physical and Chemical Properties

Physical state:	Woven, knitted or needled fi	berglass material. Color: White to off-white to	o yellowish
Boiling Point	N/A	Specific Gravity (1-hO=1):	2.5 (+/-I)
Vapor Pressure (m	nm 1-!g): N/A	Melting Point:	1350° F / 732° C
Vapor Density (A	ir = I: N/A	% Volatile by Volume:	N/A
Evaporation Rate:	N/A	Solubility in Water:	Insoluble

Page 2 of 3



SDS

THERMO-TEC AUTOMOTIVE, INC.

www.thermotec.com

SAFETY DATA SHEET

SECTION X - Stability and Reactivity

Stability: Conditions to avoid: Incompatibility (Materials to avoid): Odor: Hazardous Decomposition of Byproducts: Hazardous Polymerization: Stable None known None known None Coatings or binders may decompose in a fire. See Section V. Will not occur

SECTION XI - Toxicological Information

Routes of Exposure: Fiberglass is a possible mechanical irritant when in contact with the skin, eyes and mouth.

NOTE: All continuous filament fiberglass used in the manufacture of Thermo-Tec products are greater than the NIOSH limit and are not respirable. NIOSH defines "respirable fibers" as greater than 5 microns in length and less than 3 microns in diameter.

Acute:	NONE:	See Section III for possible mechanical irritation	
Chronic:	NONE		
Carcinogenic:	NONE:	Studies conducted in the last I0 years have found fiberglass textiles are not considered a human carcinogen by:	
	ARC	Internal Agency for Research on Cancer	
	ACGIH	American conference of Governmental Industrial Hygienists	
	OSHA	Occupational Safety and Health Administration	

NTP National Toxicity Program Annual Report

SECTION XII- Ecological Information

Data not available. Material not considered harmful to animals, plants or fish

SECTION XIII - Disposal Considerations

Fiber glass textiles is considered an inert industrial waste. Dispose of according to local, state, or federal regulations

SECTION XIV- Transport Information

Fiber glass is not considered hazardous

SECTION XV- Regulatory Information

Fiber glass does not require hazardous product labeling, not regulated for transport.

SECTION XVI - Other Information

Date of preparation:	13 February 2015
Date of previous revision:	31 January2010

DISCLAIMER:

The information presented is a compilation of our data and data from our suppliers. It is believed to be accurate, THERMO-TEC MAKES NO WARRANTY, EXPRESSED OR IMPLIED, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTIABILITY OR FITNESS FOR PURPOSE OR USAGE It is recommended that users confirm the appropriateness of the information presented herein.

Page 3 of 3

P.O. Box 96 Greenwich, OH 44837 T: 800-274-8437 F: 419-962-4013 www.thermotec.com